

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Core drill technology

BHW 812 VV

Order no. 277.940



Core drilling machine for wet drilling

- VV electronic control: constant speed control, soft start with continuous speed control trigger, overload protection, temperature monitoring and speed selection
- Long additional handle: turns and latches in pre-set positions to absorb high torque in freehand operation
- Safety slip clutch: offers protection if the core drill is jammed
- Clamping neck: 53 mm, suitable for application in drilling stands
- Quick-fit brass coupling: for 1/2" water hose
- Integrated water feed through the drive shaft
- GFCI operator protector circuit breaker: integrated in cord
- Mechanical 2-speed gear unit and variable, electric speed setting provide optimum speeds for a wide range of drilling diameters
- Suitable for hammer-free drilling of concrete, flush fitting of junction boxes flue connections and cutting breakthroughs
- Also ideal for precise drilling holes to fix heavy-duty anchors

Technical attributes	BHW 812 VV
Power input	1800 watt
Power output	1200 watt
Speed under load 1st/2nd gear	0-1000 / 0-3800 rpm
Tool fixture	G 1/2"
Clamping neck Ø	53 mm
Max. drill hole Ø in concrete	85 mm
Max. drilling Ø masonry	185 mm
Weight	4,7 kg

Standard equipment	
1 handle	257.580
1 open-ended wrench SW 22	109.398
1 open-ended wrench SW 32	251.475
1 wrench case	258.523
1 drill depth stop	251.047
1 clamp fitting with ratchet clip and centering aid	259.491
1 GFCI operator protection circuit breaker in cord	257.373
1 plastic carry case	329.908