

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Polishers

XC 3401 VRG

Order no. 322.008



Technical attributes	XC 3401 VRG
Max. polishing pad diameter	160 mm
Velcro pad Ø	140 mm
No load speed	160-480 rpm
Orbit	8 mm
Orbit rate, without load	3200-9600 rpm
Power input	900 watt
Power output	590 watt
Weight	2,6 kg

Positive-drive orbital polisher

- VR microprocessor control: with tachogenerator constant speed control, soft start, continuous speed control trigger, restart protection after power failure, overload protection, temperature monitoring and speed selection
- 8 mm orbit for high efficiency
- Permanent direct drive for an even polished surface
- Cushioned special hook and loop pad for polishing.
- Removable, ergonomic handle and guard for optimum handling in all applications
- Low heat generation on the surface makes it ideal for temperature-sensitive paints
- Counterweight for smoother operation
- Low height and low weight
- Spindle lock

Standard equipment	
1 grip cover	332.402
1 SoftVib handle	316.857
1 bail handle	333.565
1 special velcro backing pad, 140 Ø	342.637