

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15

D-71711 Steinheim/Murr

Phone +49 7144 828-0

Fax +49 7144 25899

info@flex-tools.com

www.flex-tools.com

FLEX

Stone working

CSW 4161

Order no. 347.507



Diamond stone cutter for cutting natural and synthetic stone up to 60 mm thick

- High-performance motor: extra powerful for stone cutting and joint milling
- Continuous cutting depth adjustment of 15 - 60 mm
- For straight cuts in natural and synthetic stone slabs up to 60 mm thick, or up to 54 mm depth with a guide rail
- Light alloy guard and guide fence
- Rubber end sleeve prevents ingress of spray water
- Water supply: for an effective cooling of the diamond blade
- Quick-fit brass coupling: for 1/2" water hose
- GFCI operator protector circuit breaker: integrated in cord
- Ideal for window sills, work tops, facing stones, terrazzo slabs in garden and landscaping, cleaning flooring joints
- Spindle lock

Technical attributes	CSW 4161
Diamond cutting disc diameter / arbor (inside diameter)	170 / 22,2 mm
Cutting depth / with guide fence	60 / 54 mm
No load speed	6200 rpm
Power input	1400 watt
Power output	840 watt
Weight	4,5 kg

Standard equipment	
1 diamond cutting disc with segmented cutting edge	347.515
1 wrench for saw blade change	359.343
1 parallel stop	350.613
1 plastic system case	353.302
1 case insert	353.310

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Stone working

Accessories

Diamond cutting disc



With segmented cutting edge, vibration-dampened. For granite, marble, sandstone, concrete.

Dimensions QTY/PKG: Order no.
in mm:

170 Ø x 22,2 1 347.515



With closed cutting edge for a clean wet-cut, suitable for tiles, marble plates and ceramics.

Dimensions QTY/PKG: Order no.
in mm:

170 Ø x 22,2 1 367.214

Connector for guide fence GRS



Precise metal connector for connecting two guide rails GRS. When not in use, the connector can be parked in the guide rail with the included tool wrench SW 5 - screw driver.

QTY/PKG: Order no.

1 353.272

FLEX Elektrowerkzeuge GmbH

Bahnhofstrasse 15
D-71711 Steinheim/Murr
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX

Stone working

Guide fence GRS



Precise aluminium profile with anodized sliding coating and guide rib.. Plugged rubber lip as contact edge at the marking, anti slip protection on the bottom. Connector 353.272 can be used to extend the guide rails as required.

Type:	Length in mm:	QTY/PKG:	Order no.
GRS 160	1600	1	359.351
GRS 80	800	1	353.280

Plastic system case



System case with insert for machine and accessories.

QTY/PKG:	Order no.
1	353.302