

## Laser range finder

### ADM 60 Li

Order number 447.862



#### Technical attributes

Precision	± 3 mm
Max. working range	0,15 - 60 m
Laser class	2
Visible laser diodes	< 1 mW, 635 nm
International Protection	IP 54
Integrated battery	3,7 V 500 mAh / Li-Ion
Weight	0,13 kg

#### Standard equipment

1 USB-cable	1 piece
1 USB-charger	1 piece
1 carrying bag	1 piece

#### Laser range finder

- + Quick determination of dimensions on construction sites
- + Simple operation
- + Length, area and volume calculation
- + Determining heights with indirect distance measurement (single and double pythagoras)
- + Painter function, automatic sum calculation of individual wall surfaces with the same height
- + Continuous measuring mode
- + Switchable units of measurement in m/mm, inches/feet
- + Has 4 reference points
- + Minimum / maximum function
- + Automatic stop
- + Illuminated four-line display
- + Dust- and splash-proof housing
- + Timer for tripod measurements
- + 1/4" connection thread for tripods

## Accessories

### Laser wall bracket

Order number 428.167



Magnetic wall bracket made of plastic with 1/4" and 5/8" device connection.

#### Technical attributes

QTY/PKG	1
---------	---

### Laser tripod adapter

Order number 398.608



5/8" internal thread on 1/4" external thread for using the laser on the elevator tripod (398.616).

#### Technical attributes

QTY/PKG	1
---------	---