

Brushing machine TRINOXFLEX

BBE 14-3 110

Order number 471.097



Technical attributes

| | |
|--------------------|-----------------------|
| Power input | 1400 watt |
| Power output | 880 watt |
| Max. tool Ø | 120 mm |
| Tool width | 100 mm |
| Tool fixture | 19 mm |
| No load speed | 1000-3500 rpm |
| Cable length | 4,0 m |
| Size (W x L x H) | 335 x 190 x 210 mm |
| Weight | 2,9 kg |

Brushing machine TRINOXFLEX

- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Unique tool attachment with quick-action coupling for tool-free change of the system attachments: for burnishing, pipe belt sanding and brushing
- + Brush attachment with detachable protective cover and suction connection Ø 32 mm for low-dust work. Including guide stop for calendaring narrow workpieces for a rectilinear grinding pattern
- + Tool-free grinding tool change via a patented quick-change system
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Spindle lock
- + For low-dust work in the metal and stainless steel area. Also for brushing, structuring and cleaning wood surfaces

Standard equipment

| | |
|------------------------------|---------|
| 1 brushing attachment BB 110 | 461.555 |
| 1 carrying case L-BOXX® 238 | 414.093 |
| 1 case insert | 451.991 |