

Brushing machine TRINOXFLEX

BBE 14-3 110

Order number 471.097



Technical attributes

Power input	1400 watt
Power output	880 watt
Max. tool Ø	120 mm
Tool width	100 mm
Tool fixture	19 mm
No load speed	1000-3500 rpm
Cable length	4,0 m
Size (W x L x H)	335 x 190 x 210 mm
Weight	2,9 kg

Brushing machine TRINOXFLEX

- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Unique tool attachment with quick-action coupling for tool-free change of the system attachments: for burnishing, pipe belt sanding and brushing
- + Brush attachment with detachable protective cover and suction connection Ø 32 mm for low-dust work. Including guide stop for calendering narrow workpieces for a rectilinear grinding pattern
- + Tool-free grinding tool change via a patented quick-change system
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Spindle lock
- + For low-dust work in the metal and stainless steel area. Also for brushing, structuring and cleaning wood surfaces

Standard equipment

1 brushing attachment BB 110	461.555
1 carrying case L-BOXX® 238	414.093
1 case insert	451.991