

FLEX-Elektrowerkzeuge GmbH  
Bahnhofstraße 15  
71711 Steinheim  
Phone +49 7144 828-0  
Fax +49 7144 25899  
info@flex-tools.com  
www.flex-tools.com

**FLEX**  
Das Original

## Cordless basic motor TRINOXFLEX 18,0 V

### BME 18.0-EC/5.0 Set

Order number 504.505



Technical attributes	
Battery voltage	18 V
Battery capacity	2,5 / 5,0 Ah
Max. tool Ø	125 mm
Tool width	50 mm
Tool fixture	Quick-fit coupling
No load speed	1700 / 2390 / 3080 / 3760 rpm
Weight without battery	1,7 kg

Standard equipment	
2 batteries 5.0 Ah AP 18.0/5.0	445.894
1 charger CA 10.8/18.0	417.882
1 carrying case L-BOXX® 238	414.093
1 case insert TKE BF140, BR50, BS50, LK152	502.812
1 case insert	502.804

### Cordless basic motor TRINOXFLEX 18,0 V

- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Brushless motor with greater efficiency and a longer service life
- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Unique tool attachment with quick coupling for tool-free change of the four system attachments for satin finishing and pipe belt grinding, for grinding with a belt file or fillet weld grinder
- + Toolless attachment changing via a patented quick-change system
- + Perfect dust protection thanks to removable protective metal grille
- + LED battery capacity display
- + Spindle lock
- + FLEX battery system: suitable for all 18,0 V battery packs