

Pipe belt sander and belt file TRINOXFLEX Set

BRE 8-4 INOX Set

Order number 453.463



Technical attributes

Power input	800 watt
Power output	325 watt
Belt speed	3-8 m/sec
Belt dimensions	533 x 4 / 9 / 30 mm
Pipe Ø max.	50 mm
No load speed	1400-4000 rpm
Cable length	4,0 m
Weight	2,6 kg

Standard equipment

1 sanding attachment, pipe belt BR 50	459.585
1 sanding attachment belt file BF 140	459.593
1 replacement roller set BR 30 Set	459.607
2 sanding belts ZIRCOFLEX P 60, 4 mm	2 pieces of 303.615
2 sanding belts ZIRCOFLEX, P 120, 4 mm	2 pieces of 303.623
2 sanding belts ZIRCOFLEX, P 60, 9 mm	2 pieces of 257.105
2 sanding belts ZIRCOFLEX, P 120, 9 mm	2 pieces of 257.102
2 sanding belts ZIRCOFLEX, P 60, 30 mm	2 pieces of 255.328
2 sanding belts ZIRCOFLEX, P 120, 30 mm	2 pieces of 255.329
1 sanding belt MESHFLEX A 240, 9 mm	1 piece of 318.663
1 sanding belt MESHFLEX A 240, 30 mm	1 piece of 318.647
1 side handle	194.034

Pipe belt sander and belt file TRINOXFLEX Set

- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing, pipe belt sanding, filing
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Sanding belt replacement: quick and tool-free
- + Sanding belt dimension: 533 x 4 - 30 mm
- + High-quality, spring-mounted sanding arm: light alloy with 2 deflection rollers. For optimum wrap-round on pipes, up to max. 270°
- + Spindle lock

FLEX-Elektrowerkzeuge GmbH
Bahnhofstraße 15
71711 Steinheim
Phone +49 7144 828-0
Fax +49 7144 25899
info@flex-tools.com
www.flex-tools.com

FLEX
Das Original

1 hexagon socket wrench, SW 4

1 hexagon socket wrench, SW 4 102.229

1 hexagon socket wrench, SW 5 115.460

1 hexagon socket wrench, SW 6 104.167

1 carrying case L-BOXX® 136 414.085

1 case insert 457.337