

Burnishing machine TRINOXFLEX

BSE 8-4 50

Order number 453.404



Technical attributes

Power input	800 watt
Power output	325 watt
Max. tool Ø	125 mm
Tool width	50 mm
Tool fixture	19 mm
No load speed	1400-4000 rpm
Cable length	4,0 m
Weight	2,3 kg

Standard equipment

1 sanding attachment for burnishing BS 50	459.577
1 hexagon socket wrench, SW 4	102.229

Burnishing machine TRINOXFLEX

- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing, pipe belt sanding, filing
- + Variably adjustable burnishing attachment, allows working close up to the edge with narrow rollers, incl. edge guide
- + Tool-free grinding tool change via a patented quick-change system
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Adjustable guard: for sanding tools up to Ø 125 mm
- + Spindle lock
- + For optimum finishing of various materials, for burnishing, texturing, polishing, brushing, smoothing, de-rusting and deburring steel and stainless steel surfaces