

Universal rotary hammer drill, 2,5 kg, SDS-plus

CHE 2-28 R SDS-plus

Order number 461.490



Universal rotary hammer drill, 2,5 kg, SDS-plus

- + Light 800 watt hammer drill and chisel hammer, pistol-shaped with the clockwise/anticlockwise rotation function
- + Clockwise/anti-clockwise rotation with switchover via carbon brush reverser. As a result, almost identical torque in both directions of rotation
- + Drilling chuck can be removed without tools
- + Quick tool change: universal application, with SDS Plus drill chuck or 13 mm quick-release chuck
- + Hammer drilling
- + Depth limit gauge: for precision drilling
- + Rotation stop for chiselling
- + Max. drilling range up to 28 mm in concrete
- + Accelerator switch with lock-on function
- + Ideal for drilling and hammer drilling, diameters from 4-18 mm in masonry and concrete for dowel fixings or through-holes.
- + For light-duty chiselling work when removing plaster and tiles

Technical attributes

No load speed	0-1300 rpm
Blows per minute	0-4000 bpm
Single impact energy (EPTA)	2,7 J
Max. drill hole Ø in concrete	28 mm
Max. drill hole Ø in steel	13 mm
Max. drill hole Ø in wood	30 mm
Power input	800 watt
Tool fixture	SDS-plus
Chuck Ø	1,5 - 13 mm
Size (W x L x H)	390 x 83 x 205 mm
Cable length	4,0 m
Weight	2,8 kg

Standard equipment

1 chuck BF CHE2	468.843
1 chuck BF SDS-plus CHE2	468.835
1 handle	417.661
1 drill depth stop	417.769
1 carrying case L-BOXX® 136	414.085
1 case insert	469.033