

## Handy-Giraffe® wall and ceiling sander with interchangeable head system

### GCE 6-EC Kit

Order number 504.114



### Handy-Giraffe® wall and ceiling sander with interchangeable head system

- + Electronic control: stepless speed selection, constant speed, overload protection, re-start protection and temperature monitoring
- + Brushless motor with greater efficiency and a longer service life
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Grip hood for easy handling and precise working
- + Fitted with innovative interchangeable head system. Sanding heads are attached and removed with a click
- + Effective dust extraction from between the brush ring and the sanding pad prevents clogging of the abrasive and promotes a dust-free working environment
- + Defined hose guidance and effective dust extraction due to large hose cross-section. The suction hose is directly attached to the tool by the FLEX clip-system
- + Lightweight and easy-to-use on small surfaces, tight spaces
- + Ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting
- + Machine without sanding head as an addition for the Giraffe® GE 7

#### Technical attributes

Power input	600 watt
Power output	400 watt
No load speed	1100-1650 rpm
Orbit rate, no load (MH-T)	3800-5700 opm
Orbit rate, no load (MH-X)	3100-4600 opm
Sanding disc Ø	225 mm
Cable length	4,0 m
Size (W x L x H)	300 x 110 x 150 mm
Dimensions with head (L x W x H)	360 x 260 x 210 mm
Weight excluding head	1,2 kg

#### Standard equipment

1 carrying case L-BOXX® 374	414.107
1 case insert	500.798