

## Concrete wall and ceiling grinder Giraffe® with interchangeable head system

### GDE 10 Set Thermo-Jet

Order number 504.211



#### Technical attributes

Power input	1010 watt
Power output	590 watt
No load speed DGH-R	5800-8700 opm
No load speed DSH-R	1700-2500 opm
Disc Ø	150 mm
Tool fixture	28 mm Ø
Tilt angle on the head	100 °
Length	1490 mm
Cable length	4,0 m
Weight excluding head	3,6 kg

#### Concrete wall and ceiling grinder Giraffe® with interchangeable head system

- + Electronic: controlled constant speed, soft-start, overload protection and speed selection with adjuster wheel
- + Very handy, light-weight machine with optimum ease of operation. Provides comfortable and ergonomic working conditions
- + With an innovative interchangeable head system with segment for close up to edges. Sanding heads can be fitted and removed with one click
- + Easy guiding: by optimal balance between motor and sanding head
- + Reliable force transmission and high flexibility thanks to the flexible drive shaft from. For decades established "FLEX technology". Thanks to this design principle the weight on the head of the Giraffe is reduced to a minimum. This facilitates handling.
- + Gimbal-mounted sanding head provides high flexibility and optimum adjustment for sanding walls and ceilings.
- + Effective suction extraction ensures low-free working
- + Option of connecting the FLEX safety vacuum cleaners to the FLEX clip-system on the guide tube
- + Dust-proof on/off switch
- + Very flexible thanks to an optional 500 mm extension (accessory) for high rooms, can be attached without any tools
- + Very large areas and rooms up to 3.40 m in height can be processed thanks to the optional application of the GM 340
- + The innovative, textile transport system allows the machine and accessories to be transported effortlessly. The Giraffe® does not have to be mounted and is immediately ready for use
- + Abrasive disc for coarse sanding with high removal rate for sanding, reducing/levelling formwork unevenness, sintered layers, paints, adhesive residues, thermoplastic, graffiti, algae and other contaminants. With FLEX special flange.

#### Standard equipment

1 Thermo-Jet diamond grinding disc	504.092
1 segment sanding head DGH-R	503.819
1 segment sanding head DSH-R	503.827
1 clip-on quick clamping ring SH-FC 32	406.023
1 carrying bag	408.867