

2600 watt angle grinder T-Rex with enormous reserves of power, 230 mm

L 26-6 230

Order number 436.704



Technical attributes

Max. disc diameter	230 mm
No load speed	6500 rpm
Power input	2600 watt
Power output	1800 watt
Tool fixture	M 14
Clamping collar Ø	64 mm
Cable length	4,0 m
Size (W x L x H)	500 x 106 x 145 mm
Weight	6,35 kg

Standard equipment

1 guard grinding 230 Ø	338.729
1 SoftVib handle	325.384
1 clamping flange	338.753
1 SDS-Clic quick-clamp nut M 14	253.049
1 hexagon socket wrench, SW 6	104.167
1 pin wrench	100.110

2600 watt angle grinder T-Rex with enormous reserves of power, 230 mm

- + Microprocessor control with soft start, restart protection after power failure, overload protection, CDC-electronic feedback control
- + Anti-Kickback - this shuts down the motor on the disc being blocked
- + Robust motor housing and gearbox housing. Stable and robust steel gearbox as well as a spindle bearing protected by a metal cap also increase reliability and durability
- + Highly efficient and resilient motor for more power output
- + An additional vibration damping ring between the motor housing and rear handle reduces the vibrations.
- + SoftVib handgrip for reduced vibration can be mounted in three positions.
- + Rear shaft handle with soft padding for secure grip. The grip area turns 90° to the right and left for an optimum working position
- + Spindle lock
- + Removable covering cap for easy change of carbon brushes
- + Tool-free adjustment of safety guard
- + Cutting guard (389.625) or cover for cutting guard (446.068), as an optional accessory