

Compact renovation grinder for dust-free grinding close to edges, 125 mm

LD 16-8 125 R, Kit Turbo-Jet II

Order number 504.939



Technical attributes

Disc Ø	125 mm
No load speed	7800 rpm
Power input	1600 watt
Power output	950 watt
Tool fixture	M 14
Cable length	4,0 m
Weight	3,1 kg

Standard equipment

1 Turbo-Jet grinding disc II	453.773
1 dust extraction hood with brush ring	498.475
1 bail handle	1 piece
3 cable clips	252.188 (3x)
1 hexagon socket wrench, SW 4	102.229
1 pin wrench	392.537
1 carrying case L-BOXX® 238	414.093
1 case insert	414.131

Compact renovation grinder for dust-free grinding close to edges, 125 mm

- + Electronic control: with tachogenerator constant speed control, soft start, overload protection and temperature monitoring
- + Dust extraction: prevents dust nuisance, reduces disc wear, keeps the concrete pores open for the new coating
- + Reliable 1600 watt high-performance motor with sufficient power reserves
- + Anti-Kickback - this shuts down the motor on the disc being blocked
- + Guard with pivoting segment to allow grinding right up to the wall. Height-adjustable to the disc height and for optimum dust extraction
- + With steplessly adjustable, vibration-proof, ergonomic bail handle, for optimum handling and machine control
- + For fast hose connection. FLEX clip connection for Ø 32 mm snap connection included in the standard equipment
- + Recessed spindle lock, to avoid unintentional activation
- + Ideally suited for processing walls, ceilings and floors. Efficient and economic working thanks to optimum coordination between machine and sanding disc
- + Turbo-Jet grinding disc with optimum removal rate. The large number of diamond segments provides a considerably quieter operating performance and a more attractive sanding pattern. Ideal for surface grinding on mineral substrates.