

## Delta sander with speed control in set

### ODE 100-2 Set

Order number 429.864



#### Technical attributes

Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing plate	100 x 150 mm
Sanding media fixing	velcro
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Weight	1,2 kg

#### Delta sander with speed control in set

- + Material-compatible sanding speed by adjustable speed. No elaborate rework due to damaged surfaces
- + Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- + Small and particularly light one-handed unit with excellent ergonomics and special balancing for low-vibration operation to make work effortless and reduce the stress on joints of the user
- + Impact-resistant filter cartridge with exchangeable PES filter allows simple dust disposal or cleaning of the filter as well as maximum service life
- + PES filter cartridge with cyclone function for dust-free and efficient working
- + External dust extraction Ø 27 mm, antistatic suction hose SH 27x4m AS (379.395) can be connected
- + High-performance sanding pad: highly durable and abrasion-resistant
- + Especially suitable for overhead work

#### Standard equipment

1 velcro backing plate	436.321
1 PES microfilter cartridge with filter	407.984
1 sanding paper SELECTFLEX P 80	1 piece of 380.997
1 sanding paper PURFLEX P 120	1 piece of 381.136
1 carrying case L-BOXX® 136	414.085
1 case insert	412.198