

Compact delta sander with speed control

ODE 2-100 EC

Order number 468.916



Technical attributes

Power input	260 watt
No load speed	8000 - 12000 rpm
Orbit rate, no load	16000 - 24000 opm
Orbit	2,0 mm
Backing plate	100 x 150 mm
Sanding media fixing	velcro
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Size (W x L x H)	188 x 90 x 120 mm
Weight	1,2 kg

Compact delta sander with speed control

- + Brushless motor with greater efficiency and a longer service life
- + Electronics: Speed preselection with 4 settings, constant speed control by means of tachogenerator, soft start, restart protection
- + Sanding speed suitable for the material thanks to electronic speed adjustment
- + Lightweight, compact one-handed delta sander, very ergonomic and low-vibration thanks to special balancing for fatigue-free and joint-friendly work
- + Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- + Effective dust extraction thanks to integrated extractor for dust-free working with filter cartridge
- + Impact-resistant filter cartridge with exchangeable PES filter allows simple dust disposal or cleaning of the filter as well as maximum service life
- + External dust extraction Ø 27 mm, antistatic suction hose SH 27x3,5m AS (445.045) can be connected
- + Hook & loop backing pad with 10-hole system for optimum extraction, suitable for all standard abrasives
- + Equipped with disc brake, as a result no unwanted sanding marks are produced on the workpiece and expensive corrective finishing is not required
- + E-signal switch for simple, safe operation with quick-stop function prevents trailing of the backing pad
- + Especially suitable for overhead work

Standard equipment

1 velcro backing plate	468.991
1 PES microfilter cartridge with filter	486.833