

Random-orbit sander with speed control in set, 125 mm

ORE 125-2 Set

Order number 429.880



Technical attributes	
Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing pad	Ø 125 mm
Sanding media fixing	velcro
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Weight	1,2 kg

Random-orbit sander with speed control in set, 125 mm

- + Sanding speed to suit the material due to speed control. No more damaged workpieces.
- + Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- + Small and particularly light one-handed unit with excellent ergonomics and special balancing for low-vibration operation to make work effortless and reduce the stress on joints of the user
- + Impact-resistant filter cartridge with exchangeable PES filter allows simple dust disposal or cleaning of the filter as well as maximum service life
- + PES filter cartridge with cyclone function for dust-free and efficient working
- + External dust extraction Ø 27 mm, antistatic suction hose SH 27x4m AS (379.395) can be connected
- + High-performance sanding pad: highly durable and abrasion-resistant
- + Equipped with disc brake, as a result no unwanted sanding marks are produced on the workpiece and expensive corrective finishing is not required
- + Especially suitable for overhead work

Standard equipment	
1 velcro backing pad	436.348
1 PES microfilter cartridge with filter	407.984
1 sanding paper SELECTFLEX P 80	1 piece of 380.547
1 sanding paper PURFLEX P 120	1 piece of 380.687
1 carrying case L-BOXX® 136	414.085
1 case insert	412.198