

## Palm sander with speed control in set

### OSE 80-2 Set

Order number 429.848



#### Technical attributes

Power input	200 watt
No load speed	8000 - 13000 rpm
Orbit rate, no load	16000 - 26000 opm
Orbit	2,0 mm
Backing plate	80 x 130 mm
Sanding media fixing	velcro
Dust extraction connection	Ø 27 mm
Cable length	4,0 m
Size (L x H)	150 x 155 mm
Weight	1,2 kg

#### Palm sander with speed control in set

- + Material-compatible sanding speed by adjustable speed. No elaborate rework due to damaged surfaces
- + Ergonomically designed, handy grip cover with soft grip insert ensures a secure grip and good guidance
- + Small and particularly light one-handed unit with excellent ergonomics and special balancing for low-vibration operation to make work effortless and reduce the stress on joints of the user
- + Impact-resistant filter cartridge with exchangeable PES filter allows simple dust disposal or cleaning of the filter as well as maximum service life
- + PES filter cartridge for dust-free and efficient working
- + External dust extraction Ø 27 mm, antistatic suction hose SH 27x4m AS (379.395) can be connected
- + High-performance sanding pad: highly durable and abrasion-resistant
- + Especially suitable for overhead work

#### Standard equipment

1 velcro backing plate, 80x130 8F	436.305
1 PES microfilter cartridge with filter	407.984
1 sanding paper SELECTFLEX P 80	1 piece of 380.776
1 sanding paper PURFLEX P 120	1 piece of 380.903
1 carrying case L-BOXX® 136	414.085
1 case insert	412.198