

Random orbital polisher with positive-action drive

XCE 10-8 125

Order number 418.072



Technical attributes

| | |
|-----------------------------|---------------|
| Max. polishing pad diameter | 160 mm |
| Max. back-up pad diameter | 150 mm |
| Orbit | 8 mm |
| No load speed | 140-430 rpm |
| Orbit rate, no load | 2900-8600 opm |
| Power input | 1010 watt |
| Power output | 590 watt |
| Cable length | 4,0 m |
| Weight | 2,6 kg |

Random orbital polisher with positive-action drive

- + VR microprocessor control: with tachogenerator constant speed control, soft start, continuous speed control trigger, restart protection after power failure, overload protection, temperature monitoring and speed selection
- + 8 mm polishing stroke, positive-action drive provides high abrasive power without creating any holograms
- + Cushioned special hook and loop pad for polishing.
- + Counterweight for smoother operation
- + Basic tool for tackling the most common surface problems through to finishing without creating any holograms
- + Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- + Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- + Optimised air flow for optimum cooling of motor and gear. No annoying exhaust air for the user
- + Low heat generation on the surface makes it ideal for temperature-sensitive paints

Standard equipment

| | |
|-------------------------------------|---------|
| 1 special velcro backing pad, 125 Ø | 442.445 |
|-------------------------------------|---------|