

## Roto random orbit polisher for small areas

### XFE 7-12 80 P-Set

Order number 447.137



### Roto random orbit polisher for small areas

- + VR microprocessor control: with tachogenerator constant speed control, soft start, restart protection after power failure, overload protection, temperature monitoring and speed selection
- + Free-spinning drive for hologram-free finishing
- + 12 mm orbit for high efficiency
- + Cushioned special hook and loop pad for polishing.
- + Counterweight for smoother operation
- + Optimised air flow for optimum cooling of motor and gear. No annoying exhaust air for the user
- + Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- + Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- + With rubberised resting bar for safe setting down
- + Low heat generation on the surface makes it ideal for temperature-sensitive paints
- + Especially suitable into the spot-repair area and for difficult shapes. Ideal auxiliary for larger polishers

#### Technical attributes

Max. polishing pad diameter	80 mm
Max. back-up pad diameter	75 mm
Orbit	12 mm
No load speed	1800-5500 rpm
Orbit rate, no load	3600-10800 opm
Power input	700 watt
Power output	420 watt
Size (L x H)	320 x 120 mm
Cable length	4,0 m
Weight	2,1 kg

#### Standard equipment

1 special velcro backing pad, 75 Ø	454.141
1 polishing sponge PSX-G 80	1 piece of 434.264
1 polishing sponge PS-0 80	1 piece of 434.302
1 polishing sponge PS-R 80	1 piece of 434.345
1 microfibre polishing cloth MW-C	317.098
1 polish P05/05-LDX 250 ml	443.271
1 sealing W02/04 250 ml	443.301
1 carrying case L-BOXX® 136	414.085
1 case insert	446.963